

## DESCRIPTION

Thickness	EN ISO 24346 [EN 428]	5mm / 7mm
Weight	EN ISO 23997 [EN430]	5mm - 7.6KG m <sup>2</sup> 7mm - 10KG m <sup>2</sup>
Tile Dimensions	EN ISO 24342 [EN 427]	508mm x 508mm

## CLASSIFICATION

Norm / Product specification	-	EN ISO 10582 [EN 6491]
European classification	EN ISO 10874 [EN 685]	34/43
Fire Class	EN 13 501-1	Bfl-s1
Electrical Resistance	IEC 61340-5-1	1x10 <sup>9</sup> - 1x10 <sup>10</sup> Ω

## PERFORMANCE

Wear resistance	EN 660.2	Group T
Dimensional stability before exposure to heat	BS EN 434	0.11%
Dimensional stability after exposure to heat	BS EN 434	Average 0.19
Residual indentation	BS EN 433	0.06mm
Castor Wheel	BS EN 425	No Damage
Shore hardness	EN ISO 868	92 Shore A
Thermal conductivity	ISO 8302	0.03807m2K/W
Chemical Resistance	BS EN 423	Good
Light Fastness (Blue Wood Standard)	BS EN 20105 - B02	7BWS/5GSR
Anti Slip	BS EN 13893 Deutsche Norm DIN 51130	
Density	BS EN 436:1994	Average 1404kg/m2
Flexibility	BS EN 435	Flexibility No Cracking

## ENVIRONMENTAL ACCREDITATIONS

TVOC after 28 days	ISO 16000-6	<100 µg/m <sup>3</sup>
Certification	-	Floorscore®

## Recyclable

BRE-Green Guide Ratings A+

