

DESCRIPTION

Thickness	EN ISO 24346	5mm / 7mm
Weight	EN ISO 23997	5mm - 7KG m ² 7mm - 9.21KG m ²
Tile Dimensions	EN ISO 24342	503mm x 503mm

CLASSIFICATION

Norm / Product specification	-	EN ISO 10581
European Classification	EN ISO 10874	34/43
Fire Class	EN 13 501-1	Bfl-s1
Electrical Resistance	IEC 61340-5-1	1x10 ⁹ - 1x10 ¹⁰ Ω

PERFORMANCE

Wear Resistance	EN 660.2	Group T
Dimensional stability before exposure to heat	EN ISO 23999	0.11%
Dimensional stability after exposure to heat	EN ISO 23999	Average 0.19
Residual Indentation	BS EN 433	0.06mm
Castor Wheel	BS EN 425	Ok
Shore Hardness	EN ISO 868	>40 H _D
Thermal Conductivity	ISO 8302	0.03807m2K/W
Chemical Resistance	BS EN 423	Ok
Light Fastness (Blue Wood Standard)	BS EN 20105 - B02	7BWS/5GSR
Slip Resistance	EN 16165 app. B (DIN 51130)	R10
Density	BS EN 436:1994	Average 1404kg/m ²
Flexibility	BS EN 435	Flexibility No Cracking

ENVIRONMENTAL ACCREDITATIONS

TVOC after 28 days	ISO 16000-6	<100 µg/m ³
Certification	-	Floorscore®

CE MARKING



EN 14041

