

## DESCRIPTION

Thickness	EN ISO 24346	5mm / 7mm
Weight	EN ISO 23997	5mm - 7KG m <sup>2</sup> 7mm - 9.21KG m <sup>2</sup>
Tile Dimensions	EN ISO 24342	503mm x 503mm

## CLASSIFICATION

Norm / Product specification	-	EN ISO 10581
European classification	EN ISO 10874	34/43
Fire Class	EN 13 501-1	Bfl-s1
Electrical Resistance	IEC 61340-5-1	1x10 <sup>6</sup> - 1x10 <sup>8</sup> Ω

## PERFORMANCE

Wear resistance	EN 660.2	<2mm <sup>3</sup>
Wear group	-	Group T
Dimensional stability	EN ISO 23999-1	<0.20 No Curling
Residual indentation	EN ISO 24343-1	<0.05
Castor chair test (type W)	ISO 4918 [EN 425]	No Change
Shore hardness	EN ISO 868	>40 H <sub>D</sub>
Thermal conductivity	EN ISO 10456 [EN12524]	0.25 w/(m.K)
Colour fastness	EN ISO 26987	Ok
Slip Resistance	DIN 51130	R10
Chemical products resistance	EN ISO 26987	OK

## ENVIRONMENTAL ACCREDITATIONS

TVOC after 28 days	ISO 16000-6	<100 µg/m <sup>3</sup>
Certification	-	Floorscore®

## TECHNICAL ACCREDITATIONS



EN 14041

