	DECLARATION OF PERFORM	ANCE	
1,	Identification of the product type		
	R-Tile loose-lay interlocking PVC floor tile		
2.	Product Brands		
	Textured 9mm Industrial grade		
3.	Intended was as were after a sentencial and the sentencial		
3.	Intended use or uses of the construction product, in accordance with the specification as foreseen by the manufacturer.	e applicable harmonised technical	
	For use as floor covering in buildings (See EN 14041) according to the r	manufacturer's specifications.	
4.	Name, registered trade name or registered trademark and contact addre pursuant to article 11(5).	ess of the manufacturer as required	
	R-Tek Manufacturing Ltd. 259 Battleford Road, Benburb, Co Tyrone, B	T71 7NP	
5.	Where applicable, name and contact address of the authorised represent specified in article 12(2)	ntative whose mandate covers the tasks	
	R-Tek Manufacturing Ltd. 259 Battleford Road, Benburb, Co Tyrone, B	T71 7NP	
6.	System or systems of assessment and verification of constancy of perfoout in Annex V:	rmance of the construction product as set	
	System 1		
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified certification body that performed the initial inspection of the manufacturing plant and of factory production control, continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of constancy of performance (Fire performance only).		
	Element Materials Technology	2812-CPR-DA5011	
	Rotterdam B.V		
	Zekeringstraat 33		
	1014 B.V		
	Amsterdam Netherlands		
	Netilerlands		
	Notified body 2812	Certificate of constancy performance.	
8.	In case of the declaration of performance concerning a construction production	duct for which a European Technical	

Assessment has been issued:

N/A

Declaration of performance

Harmonised Technical Specification: EN 14041:2004/AC:2006					
Essential Characteristics	Performance	Method			
Reaction to fire	B _{FL} -S1	EN 1350-1			
Content of Pentachlorophenol	NPD	Verification not required			
Formaldehyde Emission	E1	Manufacturer's declaration			
Slip resistance	Textured – R10	DIN S1130			
Electrical behaviour	2.1 – 5.5	EN 1815 & EN 1081			
Thermal conductivity (W/mK)	NPD	EN 12524/ EN 12667			
Water-tightness	NPD	EN 13553			

	Thermal conductivity (W/mK)	NPD	EN 12524/ EN 12667		
	Water-tightness	NPD	EN 13553		
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by: SEAMUS GREENE (QUALITY MANAGER)				
	(Name and Function)				
	R-TEK Manufacturing Ltd - OI 02 2	<u>.</u>	Seaming Green	2	
	(Place and date of issue)	•••	(Signature)		